C

# **Declaration of Performance**

No.: 1123-1523 EN 846-5:2012

	Deciaration of i	CHOITIANCC	EN 846-5:2012 EN 846-7:2012
1. Product Type: Unique identifi Type:	cation code of the Product	SURETWIST EXTRA AS	
element allowi	serial Number or any other ng identification of the roduct as required under	SURETWIST EXTRA AS 8/6,5mm 1123- 02/1523-02 (150mm - 450mm) SURETWIST EXTRA AS 10/8,5mm 1123- 03/1523-03 (150mm - 450mm)	
product, in acc harmonised te	or uses of the construction cordance with the applicable chnical specification, as e manufacturer.	The product SURETWIST EXTRA AS mechanical remedial wall tie is an asymmetrical dual diameter stainless steel helical wall tie, used to connect soft external substrates to harder internal walls.	
	ny, registered trade name lress of the manufacturer as Article 11(5):	SURETWIST EXTRA AS ®  Brutt Saver Hungary Kft. Pipis Hegy, 3200 Gyöngyös Hungary	
address of the	ble, name and contact authorized representative te covers the tasks specified	Construction Products Solutions International Ltd. Unit 3 Haslemere Industrial Estate, Pig Lane, Bishops Stortford, Herts, CM23 3HG, United Kingdom	
		Tel +44 (0) 1279 505514 Fax +44 (0) 1279 755190	
verification of	tems of assessment and constancy of performance construction product as set nex V:	System 3. ISO 9001:2015 No.: 03 QMS 1997e	
In case of the (DoP) concern	(Harmonised EN): declaration of performance ing a construction product narmonised standard:	Building research institute ITB Katowice NB 1488 Issued Approval number - LOK-1118-A-08 Imperial College London, Testing Centre Lucideon Ltd. regarding a statement on the structural products properties subject to the standard EN ISO 6892-1:2009 EN 845-1:2013+A1:2016 EN 846-5:2012, EN 846-7:2012	
concerning a c	declaration of performance construction product for ean Technical Assessment	Not relevant (see 7)	

### 9. Declaration of performance:

#### **Product dimensions**

Dimension mm	Types
Length	150mm to 450mm
Diameter	8/6.5mm, 10/8.5mm
Pitch	40±1 mm (Diameter 8/x), 50±1 mm (Diameter 10/x)

## **Durability**

Туре	Coating
SURETWIST Extra AS	Austenitic Stainless Steel

## Information and regulated characteristics:

When the mentioned products are used in accordance with the instructions on the product installation leaflet, the product gives the characteristics as mentioned in the table below.

SURETWIST Extra AS dual diameter / Characteristics				
Intended use	Structural Application			
Material	1.4301/1.4567 or 1.4401/1.4404			
Tensile strength	Min. declare	Min. declared value 880 MPa		
Profile Size мм	Area мм²	Yield Point N/мм²	E - Modul G Pa	
6	8	745	156.269	
8	10	745	148.813	
10	13	955	146.114	
Test Results (Tensile Loads)	Solid Clay Brick ≥ 10N/mm <sup>2</sup> ≥ 400kg/m <sup>3</sup> to EN 771-1+A1:2016 6mm 1000N, 8mm 1250N, 10mm 1500N. Mortar ≥ 27N/mm <sup>2</sup> to EN 998-2:2017 6mm 1000N, 8mm 1250N, 10mm 1500N.			
Compressive Load		according to EN 1996	v.	
Bond strength		n Report LOK-1118-A-08		
Water penetration resistance	Resistant			
Dangerous substances	No			

#### 10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Date of Issue:	Approved by:  General manager – Brutt Saver Gyöngyös – Hungary	BRUTT ®
----------------	--	---------